SecureCoin[™]

Electronic Coin Acceptor


- Ready to accept any combination of U.S. quarters and \$1 coins –
 no programming required. Pre-programmed coins provide for better
 acceptance of valid coins and rejection of unwanted coins.
- Up to 3 tokens of your choice are easily programmed in addition to pre-programmed currency coins.
- Display and keypad allow for easy setup and provide access to multiple configuration options.
- Superior solid state sensing and sizing technology provides consistent and accurate coin evaluation.
- Waterproof design for high moisture environments such as car washes.
- · Constructed of high impact plastic and stainless steel.
- · Power saving mode when idle.
- Anti-stringing sensors and logic are standard equipment and reject all attempts at improper use.
- Changes to currency coins can be updated in the field without removing the acceptor from operation.
- · No sample coins or manual adjustments are required.
- · Universal interface works with most timers.
- · Industry standard mounting.
- Available in 24 vac or 12-30 vdc versions with electronic or relay pulsing. Inhibit connection also available.
- Versions available for Canadian and Euro currency coins as well as other countries.





Model CP890U Short Drop





Panel Display:

- · Fast and easy setup, no switches.
- · Display provides diagnostic messages.
- Display and keypad allow for easy setup and provide access to multiple configuration options.
- Pulse speed can be adjusted to accommodate older timers.
- Number of pulses for pre-programmed currency coins can be set to either fixed or variable depending on which currency coins are enabled.
- Configurable token settings provide improved performance based on the characteristics of your token.

Coin Release Mechanism and Full Access to Coin Path:


- Coin Release Mechanism allows bent or damaged coins to be removed with the simple press of the mechanism.
- Full access to the coin path is readily available for cleaning and other service.



CP990U



Model	CP990U	CP890U
A	2"	2.6"
В	7.7"	5"
С	3.9"	3.9"
D	2.26"	-
	2 9 9	





CP890U

